



Product Data Sheet		Group BIa - Annex G EN14411:2016	 
Intended use of the material: Floor and wall tiles for interior			
<p>Type of material: Glazed porcelain tiles, dry pressed.</p> <p>Format: 60x60 (W = 595x595x10 mm).</p>			
Series : Blake			
Kind of test		Referring standard	Standard value
Dimensions	Length and width tolerances	UNI EN ISO 10545-2	± 0,6%; ± 2,0 mm
	Thickness tolerances		± 5%; ± 0,5 mm
	Tolerance straightness of the sides		± 0,5%; ± 1,5 mm
	Squareness and flatness tolerances		± 0,5%; ± 2,0 mm
Physical Properties	Determination of water absorption	UNI EN ISO 10545-3	≤ 0,5%
	Determination of breaking strength	UNI EN ISO 10545-4	≥ 1300 N
	Determination of modulus of rupture	UNI EN ISO 10545-4	≥ 35 N/mm ²
	Det. of resistance to surface abrasion glazed tile	UNI EN ISO 10545-7	Classification: PEI IV
	Thermal Shock resistance	UNI EN ISO 10545-9	resistant
	Determination of frost resistance	UNI EN ISO 10545-12	resistant
	Determination of scratch hardness Mohs scale	Mohs - EN101	Scratch Mohs: /
	Determination of slip resistance		
	Determination of dynamic coefficient of friction (DCOF)	BOT 3000 (ANSI A 137.1:2012)	≥ 0.42
	Determination of the property antislip of bathed zones on which it walks knots on foot	DIN 51097 (a/b/c)	Slide angle: / Classification: /
	Determination of anti-slippery characteristic (work's zone with high risk of slippery)	DIN 51130	Slide angle: / Classification: /
	Determination of static coefficient of friction	ASTM C1028	Dry Neolite: / Wet Neolite: /
Chemical Resistance	Determination of resistance to stains		
	Stains having tracing action (pastes) <i>Green staining agent in light oil</i>	UNI EN ISO 10545- 14	Classification: 5
	Stains having chemical/oxidizing action <i>Lodine/alcohol solution, 13 g/l</i>		Classification: 5
	Stains having filming action <i>Olive oil</i>		Classification: 5

A Brand of:  VICTORIA PLC

ASCOT GRUPPO CERAMICHE S.r.l.

41014 Solignano di Castelvetro (Mo) Italy
Via Croce, 80

PH. +39 059 77 84 11
FAX +39 059 77 84 44/43

info@domceramiche.it
domceramiche.it

STABILIMENTI:

41014 Solignano di Castelvetro (Mo) Italy
Via Croce, 80

41014 Solignano di Castelvetro (Mo) Italy
Strada Statale 569, 167/A

Capitale sociale Eur 10.000 int.ver. - Reg. Imprese e Cod. Fisc. 10874040966
PIVA Intracomunitaria IT 10874040966 - R.E.A. MO-427794
Soggetta a direzione e coordinamento di Victoria Plc



	Determination of chemical resistance		
	Household chemicals <i>Ammonium chloride</i>	UNI EN ISO 10545- 13	Classification: A
	Swimming pool salts <i>Sodium hyupochlorite</i>		Classification: A
	Determination of resistance acids and alkaline		
	Citric acid	UNI EN ISO 10545- 13	Classification: LA
	Hydrochloric acid		Classification: HA
	Potassium hydroxide		Classification: HA
	The values in the table refer to the tests performed on color <i>Bianco Veined</i>		

Quality Management Office
Pasquale Matera

ASCOT GRUPPO CERAMICHE S.r.l.

Via Croce, 80
41014 Solignano di Castelvetro (MO) ITALY
Tel. +39 059 77.84.11 - Fax +39 059 77.84.44/43
E-mail: info@ascot.it - <http://www.ascot.it>
P.IVA intracomunitaria IT 1 0 8 7 4 0 4 0 9 6 6

A Brand of:  VICTORIA PLC

ASCOT GRUPPO CERAMICHE S.r.l.

41014 Solignano di Castelvetro (Mo) Italy
Via Croce, 80

PH. +39 059 77 84 11 info@domceramiche.it
FAX +39 059 77 84 44/43 domceramiche.it

STABILIMENTI:

41014 Solignano di Castelvetro (Mo) Italy
Via Croce, 80

41014 Solignano di Castelvetro (Mo) Italy
Strada Statale 569, 167/A

Capitale sociale Eur 10.000 int.ver. - Reg.imprese e Cod. Fisc. 10874040966
PIVA Intracomunitaria IT 10874040966 - R.E.A. MO-427794
Soggetta a direzione e coordinamento di Victoria Plc

