













	Proprietà fisico-chimiche physical chemical properties Propriétés physico chimiques Physisch chemische	Metodo di prova Standard of test Norme du test Testnorm	UNIVERSAL
	Dimensioni / Dimensions / Dimensions / Abmessungen Lunghezza e Larghezza Lenght and Width Longuer et Largeur Länge und Breite	ISO10545-2 ± 0,3% max	± 0,3% max
	Spessore Thickness Epaisseur Stärke	± 5% max	± 5% max
	Assorbimento d'acqua Water absorption Absorption d'eau Wasseraufnahme	ISO 10545 -3 ≤ 0,5%	≥ 0,1%
	Resistenza al gelo Frost resistance Rèistance au gel Frostbeständigkeit	ISO 10545 -12	Resistente Resistant Rèistant Widerstandfähig
	Resistenza agli sbalzi termici Resistance to Thermal shock Rèistance aux écarts de température Temperaturwechselbeständigkeit	ISO 10545 - 9	Resistente Resistant Rèistant Widerstandfähig
	Resistenza all'abrasione Resistance to abrasion Rèistance à l'abrasion Bestaendigkeit gegen abrieb	ISO 10545 - 7	Classe 4 Class 4 Classe 4 Gruppe 4
	Resistenza alle macchie Resistance to stains Rèistance aux taches Fleckenbeständigkeit	ISO 10545 - 14	Classe 5 Class 5 Classe 5 Gruppe 5
	Resistenza ai prodotti chimici di uso domestico Resistance to surface to househod chemicals Rèistance aux produits chimiques ménagers Beständigkeit gegen haushaltschemikalien	ISO 10545 - 13	Classe A Class A Classe A Gruppe A
	Resistenza agli acidi e alle basi a bassa concentrazione resistance to low concentrations of acid and bases Rèistance aux acides et aux bases à faible concentration Beständigkeit gegen niedrig konzentrierte säuren und basen		Classe LA -HA Class LA -HA Classe LA -HA Gruppe LA -HA
	Resistenza alla flessione Modulo di rottura/Carico di rottura Bending strength Modulus of rupture/Braking of rupture Rèistance à la flexion Module de rupture/Charge de rupture Biegezugfestigkeit Bruchmodul/Last	ISO 10545 - 4 R ≥ 35 N/mm ² S ≥ 1300 N	R = 52,3 N/mm ² S = 2672,8 N

	Fattore di resistenza alla scivolosità Anm-skeed resistance grade Gre' de resistance à la glissance Rutschfestigkeit	DIN 51130	R 9
	Ignifugo Fire resistant Résistant au feu Feuerfest		Resistente Resistant Résistant Widerstandfähig
	Igienico e facilmente pulibile Hygienic and easy to clean Sain et facile à nettoyer Hygienisch und einfach zu reinigen		Conforme Compliant Conforme Konform